

# L-200

*Low-Temp Dehumidification Kiln*

*Starting at*  
**\$7,995**

## About The L200

For larger drying needs, the L200 models allow you to dry your lumber down to 6-8% moisture content for pennies per board foot. These compact, high-performance dehumidification systems will dry between 1,500 and 4,000 board feet of lumber.

Available in two options, the L200S includes two circulating fans, a kiln control, and a powered vent kit. While the L200M adds upgraded controls with moisture probes.

## Whats Included:

- ☒ L200 Dehumidification Kiln
- ☒ Kiln Control
- ☒ Two Circulating Fans
- ☒ Powered Vent



## Learn More:



12 Stevens Road  
Brewer, ME 04412



(800) 777-6953



kilnsales@nyle.com  
www.nyledrykilns.com

# Specifications

Load Capacity	For softwoods and fast-drying hardwoods (Pine or Poplar) 1,500 - 2,000 BF For slow-drying hardwoods (Oak) 4,000 BF
Nominal Water Removal	250 lbs. (114 kg) per 24 hours
Drying Time	4/4 Green Pine - 80% to 8% in approximately 12 days. 4/4 Green Oak - 65% to 8% in approximately 35 days.
Drying Temperature Range	70° - 120° F (21° - 49° C)
Heat Treating Capabilities	An Auxiliary heater can be used to set the pitch, sterilize the load (kill bugs) and for preheating. (Up to 160° F)
Compressor Nominal HP	2 HP
Internal Blower Motors	1/3 HP; 1,800 cfm
Auxiliary Heat	4,000 watts
Circulating Fans	Two Included: 16" 1/3 HP, 1,800 cfm
Over Temperature Vents	One power vent system included (includes exhaust and intake)
Power Requirements	240V, 60 Hz, Dedicated 40A Required.
Shipping Weight	340 lbs.
Dimensions (H x L x W)	37" x 32 ½" x 20 ½" (base unit only)

## L200 Accessories:



### Fan Kit:

Fully automated fan kit includes 16" housings 16" fan blade, 1/3 HP motor and motor starter.



### Heat Booster Package:

Used to set pitch, sterilize and faster heating of larger chambers.



### Moisture Probes:

Allows the monitoring of the moisture content of select boards in the pack.